navigo

12VS

Open FiberglassTenders



Number of Chambers : 3 + 1Shaft Length Option 1: 15"/38.1cm Shaft Length Option 2:20"/50.8cm **Overal Beam Person Capacity** : 6 : 6′/ 1.82m RDC Design Category: C Inside Length Weight : 202lb / 92kg : 8'9"/ 2.67m

Inside Beam Recommended HP : 20hp / 14.9kw

Tube Diameter : 18"/ 0.46m Maximum HP : 30hp / 22.4kw

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat
- Diamond Shape Non Skid Deck
- Plastic External Transom Plate

- Aluminum Internal Transom Plate with Security Lip Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

: 2'9"/ 0.84m

- Stainless Steal Bow Eye

- 4 Stainless Steal Davit Lifting Points
 Stainless Steal Towing Rings & Tie Downs
 Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
 3 Layer Reinforced Seams

- Paddle with Aluminum Shaft

- Paddle Holders
- Removable Stern Seat Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor

- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steal Cleat
- Lateral Fold Down Stainless Steal Cleat

- Removable Rowing Seat
- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steal Helm Unit



∢ < \vdash \sqcup

SH

؎

S

0 н