



A B I N F L A T A B L E S

lammina

9.5AL SUPERLIGHT

Aluminum Tenders



S P E C S

Overall Length	: 9'6" / 2.90m	Number of Chambers	: 3	Maximum HP	: 15hp / 11.2kw
Overall Beam	: 5'6" / 1.68m	Person Capacity	: 5	Shaft Length	: 15" / 38.1cm
Inside Length	: 6'11" / 2.11m	Weight	: 95lb / 43kg	RDC Design Category	: C
Inside Beam	: 2'6" / 0.76m	Weight with Bow Locker	: 108lb/49kg		
Tube Diameter	: 17" / 0.43m	Recommended HP	: 8hp / 6.0kw		

S T A N D A R D
F E A T U R E S

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

O P T I O N A L
F E A T U R E S

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat



www.abinflatables.com